

Powerhouse Series PHG143PeOS



し Power Systems

- Intelligent Auto-Start Controller with Generator
- Monitoring and Protection Systems Suitable for Remote Starting or Connection with shentongroup AMF Panel
- Battery Trickle Charger
- Thermostatically controlled Engine Heater
- Long Range Bunded Base Fuel Tank
- Ability to be Customised to Specific Requirements
- Output Circuit Breaker

GENERAL

The Powerhouse Series which ranges from 10 to 2230kVA, is built to a world-class standard and these remarkably competitive standby generators provide the most cost-effective solution for 'standard package' requirements.

A first-class range of diesel-powered generators for prime and standby power application which feature reliable components from leading manufacturers, these are premium products upon which your company can build its reputation.

Model PHG143PeOS		
Standby Power	kVA	143
	kW	114
Prime Power	kVA	130
	kW	104
Rated Speed	r.p.m	1500
Voltage	V	400/230
Rated Power Factor	Cos Phi	0,8
Data Sheet Number	PHG143PeOS NS Rev 1	

Prime: This rating is for the supply of continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation on the annual hours of operation and 10% overload power can be supplied for one hour in twelve hours.

Standby: This rating is for the supply of continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted. Max rating, is available for one in twelve hours Note: Standard reference conditions: 25deg C (77deg F) air inlet temperature, 152.4m (500feet) above sea level, 60% relative humidity. All engine performance data based on the above mentioned

maximum continuous ratings. Fuel consumption data at full load for diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, class A2.

In line with our policy of continuous development, we reserve the right to change specification without notice.



Powerhouse Series PHG143PeOS



THE HEART OF EVERY GREAT MACHINE

少 Power Systems



ENGINE		
Rated Output	kWm	118.7
Manufacturer		Perkins
Model		1106A-70TG1
Engine Type		Diesel 4 Strokes-Cycle
Aspiration Type		Turbo charged & intercooled
Cylinders Arrangement		6 in line
Bore & Stroke	mm	100 x 127
Displacement	L	5.99
Cooling System		Water
Compression Ratio		16.0:1
Fuel Consumption 100% PRP	l/h	30.28
Fuel Consumption 75% PRP	l/h	22.7
Fuel Consumption 50% PRP	l/h	15.9
Total Oil Capacity	L	16.5
Total Coolant Capacity	L	21
Governor	Туре	Mechanical
Air Filter	Туре	Dry Paper Cartridge
Battery Capacity	Ah	176
Battery Voltage	V	12

Perkins engines have a proven reputation within the generator industry, providing high levels of reliability and low cost of ownership. Perkins actively pursues product support excellence providing a consistent quality of support across the globe. shentongroup have used Perkins engines as our first choice product, for many years and found them to be solid, reliable and readily accepted products.



Powerhouse Series PHG143PeOS





(1)

Power Systems

)82-1,
ing

Mecc Alte has sixty years of experience in the electromechanical field, and is today at its height in the world production of synchronous alternators. Committed daily to research, development and updating activities, Mecc Alte is a testimony to constant improvement in all areas such as technology, organisation and quality. The company has ISO 9001 certification, awarded in 1996 and ISO 14001 since 2010. With 54.000 square meters of factory area, almost 850 employees and a turnover of approximately 130 million euro, Mecc Alte is a well-established company ready to challenge the markets in every product sector.



Powerhouse Series PHG143PeOS

り Power Systems

APPLICATION DATA

Exhaust System		
Maximum Exhaust Temperature	°C	576
Exhaust Gas Flow	M3/min	22.66
Maximum Allowed Back Pressure	kPa	6

Air Flows		
Intake Air Flow	m3/h	712
Cooling Air Flow	m3/s	4.2
Available Air Restriction	КРа	0.2

Fuel System		
Fuel Oil Spec		DIESEL
Fuel Tank Capacity	L	300
Autonomy @ 75% load	Hrs	13

Dimensions/Weight		
Length	mm	2500
Width	mm	1000
Height	mm	1650
Dry Weight	Kg	1390
Sound Pressure Level @ 7 mtrs	dB(A)	-

Electrical		
Output Circuit Breaker	Туре	МССВ
	Model	ABB XT3N
Full Load Current at 400V .8 p.f.	Amps	206



Power Systems

Generator Technical Data Sheet for

Powerhouse Series PHG143PeOS





 (\mathbf{l})

SG7310DS GENERATOR CONTROLLER

The SG7310DS is an Auto Start Control Module. Monitoring an extensive number of engine parameters, the modules will display warnings, shutdown and engine status information on the back-lit LCD screen, illuminated LEDs, remote PC. The modules include USB, RS232 and RS485 ports as well as dedicated DSENet[®] terminals for system expansion. The module is compatible with electronic (CAN) and non-electronic (magnetic pick up/alternator sensing) engines and offers an extensive number of flexible inputs, outputs and engine protections so the system can be easily adapted to meet the most demanding industry requirements. The full list of features includes enhanced event and performance monitoring, remote communications and dual mutual standby.

CONTROL PANEL DISPLAY FEATURES		
Engine RPM	Generator Output Current	
Engine Oil Pressure	Earth current	
Coolant temperature	Output kW	
Battery Volts	Load level %	
Run Hours/ No of starts	Output kVA	
Fuel level	Power factor	
Generator output Voltage	Load kVAr	
Frequency	kWh/kVAh/kVArh	

SG7310DS is a branded Deep Sea Electronics controller, customized to shentongroup's specific requirements. shentongroup has a long history of collaboration with Deep Sea Electronics, and endorse their products with confidence. Our experience has proved this is the market-leading controller having a perfect mix of complex capability and user simplicity.